



浙江万马天屹通信线缆有限公司

Zhejiang Wanma Tianyi Communication Wire & Cable Co., Ltd.

RG59+4\*2\*0.5CU

## Description

	Material	Diameter (mm)
Inner Conductor	CCS	0.81
Dielectric	Foamed PE	3.68
Al Foil	Bonded APA	3.88
Overall Braid	Al-Mg	
Inner Conductor	CU	4*2*0.5
Dielectric	HDPE	4*2*0.9
Jacket	PVC	6.05



## Characteristics

Capacitance	52 pF/m	SRL 5~1000MHz	18dB Min.
Velocity	82%	Impedance	75 ± 3 ohms

## Attenuation @ 20°C

Frequency MHz	Attenuation dB/100m	Attenuation dB/100ft	Frequency MHz	Attenuation dB/100m	Attenuation dB/100ft
55	7.66	2.34	500	24.51	7.48
100	10.48	3.20	600	27.10	8.27
250	17.00	5.19	750	30.56	9.32
300	18.74	5.72	1000	35.85	10.93



Fianyi Industrial Area, Faihuyuan Town, Lin'an City, Zhejiang 311300, China

Tel: +86 571 2361 6526 Fax: +86 571 6375 1363

[www.wanmatianyi.com](http://www.wanmatianyi.com)